## Material Safety Data Sheet:

```
B6100 Black Toner
MSDS Sheet \# 58358601 For Black Toner, P/N 52113701
For more information, contact Oki Data at 2000 Bishops Gate Blvd., Mount
Laurel, NJ 08054-4620
Emergency Information: call 1-800-OKIDATA; U.S. and Canada only
Hazardous Ingredients
Carbon Black (4% by weight)
CAS# Confidential
OSHA PEL: Not established
ACGIH TLV: Not established
LD50: Not Available.
LC50: Not Available.
Silica dioxide (about 2% by weight)
CAS# Confidential
OSHA PEL: Not established
ACGIH TLV: Not established
LD50: Not Available.
LC50: Not Available.
Physical Data Physical State: Solid
      Melting Point: Not available
      Boiling Point: Not available
      Vapor Pressure: Not available
      Vapor Density (Air=1): Not available
      Evaporation Rate (Butyl Acetate=1): Not available
      Specific Gravity (H2O=1): 1.1 to 1.2 at 200 C (680 F)
      Solubility in water: Not available
      Appearance and odor: Black fine powder, no odor
      Odor Threshold: Not available
Fire and Explosion Hazard Data
Minimal fire hazard. Large quantities may cause risk of dust explosion.
Flash Point (Method Used): Not applicable
Flammable Limits
  Lower Explosive Limit: Not Available
```

Upper Explosive Limit: Not Available Auto-ignition Temperature: Not Available

```
Explosion Data
  Sensitivity to Mechanical Impact: Not Available
  Sensitivity to Static Discharge: Not Available
Extinguishing Media: In case of small fire, use CO2. In case of large
fire, shut off air by spraying with water or foam.
Special Fire Fighting Procedures: Fight fire from upwind position. Avoid
inhalation of smoke or gases. Wear self-contained breathing apparatus.
Hazardous Combustion Products
    Carbon monoxide, carbon dioxide, oxides of nitrogen.
Toxicological Properties
    Routes of Entry: Inhalation, Ingestion, Eyes, Skin.
    Effects of Acute Exposure: Not available.
    Effects of Chronic Exposure: Not available.
    Exposure Limits: Not available.
    Irritancy: Not available
    Sensitization: Not available.
    Carcinogencity
    IARC
    Silica Dioxide: Group 3, Not classifiable.
    Carbon Black: Group 2B. "Possible Carcinogen."
    NTP: No components are listed.
    OSHA: No components are listed.
    Reproductive Toxicity: Not available
    Teratogenicity: Not available
    Mutagenicity: Not available
    Name of Toxicologically Synergistic Products: Not available
Reactivity Data
    Stability: Stable in general.
    Conditions to Avoid: Avoid excess heat and all sources of ignition.
    Polymerization: Will not occur.
    Hazardous Decomposition Products: Combustion products include harmful
    gases such as carbon monoxide and nitrogen oxides.
    Incompatibility: Not available.
Spill Cleanup and Disposal
Spill Cleanup
  Small Spills
    Remove sources of ignition.
    Carefully clean up spill with wet cloth, avoiding inhalation of fine
    dust.
  Large Spills
    Remove sources of ignition and keep unnecessary and unprotected
    personnel away from area.
    Wear protective gear: respirator, rubber gloves, goggles (see below)
    Vacuum the spill, then wipe up remainder with a wet cloth.
Waste Disposal
    Prevent release of material into natural waters and sewers.
    Follow appropriate federal, state, and local regulations.
    Small amounts can be incinerated. Careful! Combustion can create
```

harmful gases such as carbon monoxide and nitrogen oxides. Large amounts must be passed to a licenses waste contractor.

## Safe Handling and Use

Respiratory Protection: Not normally required. For large spills, use dust respirator during cleanup.

Protective Gloves and/or Eye Protection: Not normally required. For large spills, use rubber gloves and safety goggles during cleanup.

Ventilation: Outside of normal ventilation, not normally required.

Other Protective Equipment and/or Hygienic Practices: None Special Shipping Information: Non-hazardous. Handle container carefully to avoid shock. Do not drop. Keep dry.

## Special Precautions

Precautions for Handling or Storage: Protect from the run. Store in a cool room, under 1040F (400C).

Other Precautions: None

Emergency First Aid Procedures

Toner swallowed (ingested).

Immediately seek medical attention. Never give anything by mouth to an unconscious person. If possible, rinse out mouth and give one or two glasses of water or milk to drink.

Toner inhaled.

Remove person to fresh air. Seek medical attention.

Toner gets in the eyes.

Flush eyes with quantities of cool water for 15 minutes, keeping the eyelids open with fingers. If necessary, seek medical attention.

Toner gets on the skin.

Wash toner off the skin with plenty of cool water and soap. If necessary, seek medical attention.

Small amounts of toner on skin or clothing can easily be removed with soap and cold water. Hot water makes toner harder to remove.

## Preparation of MSDS

Date: August 23, 2002

Prepared by:

Oki Data Americas, Inc.

Engineering Services Department

2000 Bishops Gate Blvd.

Mt. Laurel, NJ 08054-4620

Tel: (856) 235-2600 Fax: (856) 222-5320 http://www.okidata.com

my.okidata.com

Posted:10/15/2002

Product(s):B6100, B6100n

Oki Data has taken care to insure that the information is complete, accurate and up-to-date. However, Oki Data assumes no responsibility for errors or omissions which may occur. All the information provided is subject to change from time to time at the sole discretion of Oki Data.

Copyright© 2000, Oki Data, Americas, Inc.