

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Identification of the

preparation

C8061A-D-X

Use of the preparation This product is a toner preparation that is used in HP LaserJet 4100/4100mfp/4101mfp series

printers.

Manufacturer information Hewlett-Packard Company

11311 Chinden Boulevard Boise, ID 83714 USA

Hewlett-Packard health effects line

(Toll-free within the US) 1-800-457-4209 (Direct) 1-503-494-7199

General information telephone number

**HP Customer Care Line** 1-800-474-6836 1-800-474-6836 (Toll-free) 1-208-323-2551 (Direct) Date prepared Feb 13, 2006 145594 MSDS number

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

Component/substance	CAS number	% by weight
Styrene acrylate copolymer	Trade Secret	40 - 50
Iron oxide	1317-61-9	40 - 50

#### 3. HAZARDS IDENTIFICATION

Acute health effects

Skin contact Unlikely to cause skin irritation. Eye contact May cause transient slight irritation

Inhalation Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust. Ingestion Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

Potential health effects

Routes of exposure Potential routes of exposure under normal use conditions are skin and eye contact; and

inhalation

Ingestion is not expected to be a primary route of exposure for this product under normal use

conditions.

Chronic health effects Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this

product as intended does not result in inhalation of excessive amounts of dust.

Carcinogenicity None of the ingredients have been classified as carcinogens according to EU, IARC, MAK,

NTP, OSHA or ACGIH.

Other information This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive

1999/45/EC, and as amended.

### 4. FIRST AID MEASURES

First aid procedures

Skin Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Material name C8061A-D-X MSDS US Creation date Apr 30, 2003 Version number 4 1/5



Eye Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for

at least 15 minutes or until particles are removed. If irritation persists, consult a physician.

**Inhalation** Move person to fresh air immediately. If irritation persists, consult a physician.

Ingestion Rinse mouth with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

### **5. FIRE FIGHTING MEASURES**

Flash point and method Not applicable

Auto ignition temperature Not applicable

**Hazardous combustion** 

products

Carbon monoxide and carbon dioxide.

**Extinguishing media** CO2, water, or dry chemical

Unsuitable extinguishing

media

None known.

Unusual fire and explosion

hazard

Like most organic material in powder form, toner can form explosive dust-air mixtures when

finely dispersed in air.

Fire fighting

equipment/instructions

If fire occurs in the printer, treat as an electrical fire.

Special firefighting procedures None established.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions Minimize dust generation and accumulation. Avoid breathing dust.

**Environmental precautions**Do not flush into surface water or sanitary sewer system. See also section 13 Disposal

considerations.

Procedures if material is

released or spilled

Slowly vacuum or sweep the material into a bag or other sealed container. If a vacuum is used, the motor must be rated as dust explosion-proof. Clean remainder with a damp cloth or vacuum cleaner. Fine powder can form explosive dust-air mixtures. Dispose of in compliance

with federal, state, and local regulations.

### 7. HANDLING AND STORAGE

**Handling** Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use

with adequate ventilation. Keep away from excessive heat, sparks, and open flames.

Storage Keep out of the reach of children. Store at room temperature in the original container. Keep the

container tightly closed and dry. Store away from strong oxidizers.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Personal protective equipment

**General** No personal respiratory protective equipment required under normal conditions of use.

**Exposure guidelines**Use in a well ventilated area.

### 9. PHYSICAL & CHEMICAL PROPERTIES

pH Not applicable
Vapor pressure Not applicable
Boiling point Not applicable

Melting point 100 - 150 °C (Softening point)

Softening point 100 - 150 °C

Material name C8061A-D-X

Creation date Apr 30, 2003

Version number 4

MSDS US

2 / 5



**Solubility** Negligible in water. Partially soluble in toluene and xylene.

Specific gravity

Flash point

Viscosity

Vapor density

Flammability

Appearance

1.5 - 1.8 (H2O = 1)

Not applicable

Not applicable

Not flammable

Fine powder

Form solid

Odor Slight plastic odor

Oxidizing properties No information available.

Other information Decomposition temperature: > 200 degrees C

Color Black

## 10. CHEMICAL STABILITY & REACTIVITY INFORMATION

**Stability** Stable under normal storage conditions.

Conditions to avoid Imaging Drum: Exposure to light

Hazardous polymerization Will not occur.

Hazardous decomposition

products

Carbon monoxide and carbon dioxide.

Incompatibility Strong oxidizers

#### 11. TOXICOLOGICAL INFORMATION

Complete toxicity data are not available for this specific formulation

Refer to Section 3 for potential health effects and Section 4 for first aid measures.

**Dermal irritation**Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Directive 67/548/EEC and as amended.

Eye irritation Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Directive 67/548/EEC and as amended.

Sensitization Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and

OSHA HCS (US).

**Chronic toxicity** No information available.

Oral toxicity LD50/oral/rat >2000 mg/kg , Not harmful. (OECD 401)

Inhalation toxicity LC50: inh/rat > 5 mg/l/4 hrs., not harmful (OECD 403).

Not classified for acute inhalation toxicity according to EU Directive 67/548/EEC and

1999/45/EC.

Carcinogenicity None of the ingredients have been classified as carcinogens according to EU, IARC, MAK,

NTP or OSHA.

Mutagenicity Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

Reproductive toxicity Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop.

65, and DFG (Germany).

# 12. ECOLOGICAL INFORMATION

Other information This product has not been tested for ecological effects.

Material name C8061A-D-X

Creation date Apr 30, 2003

Version number 4

MSDS US

3 / 5



### 13. DISPOSAL CONSIDERATIONS

**Disposal instructions**Do not shred print cartridge, unless dust-explosion prevention measures are taken. Finely

dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations. HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit

http://www.hp.com/recycle.

### 14. TRANSPORTATION INFORMATION

General Not a regulated article under United States DOT, IATA, ADR, IMDG, or RID.

IATA

Proper shipping name Not applicable

Special precautions None
Packaging exceptions None
Identification number (UN) None
Packing group N/A

#### 15. REGULATORY INFORMATION

US federal regulations

US EPA TSCA Inventory: All chemical substances in this product comply with all rules or

orders under TSCA.

US TSCA 12(b): Contains p-Xylene (CAS No. 106-42-3), subject to export notification

requirements.

State regulations This product contains no chemical substances subject to rules or orders under California

Proposition 65.

HMIS ratings Health: 1

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 1

Flammability: 1 Instability: 0

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely

hazardous substance

Section 311 hazardous

chemical

No

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Labeling Not applicable

### **16. OTHER INFORMATION**

Other information This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation

(29 CFR 1910.1200).

**Issue date** Feb 13 2006 11:57AM

Revision 3

Replaces sheet dated Feb 3 2006 1:57PM

Material name C8061A-D-X

Creation date Apr 30, 2003

Version number 4

MSDS US

4 / 5



**Disclaimer** This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in

Section 1 above and may not meet regulatory requirements in other countries.

MSDS sections updated 1. Chemical Product and Company Identification: Use of the preparation

13. Disposal Considerations: Disposal instructions

**Explanation of abbreviations** 

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

**CFR** Code of Federal Regulations

COC Cleveland Open Cup

**DOT** Department of Transportation

**EPCRA** Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

**TLV** Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Material name C8061A-D-X Creation date Apr 30, 2003

MSDS US