

# Material Safety Data Sheet

Issue Date: 2/23/2006

MSDS Number: TN305

Product Name: ET-050 Toner

Revision: [00]02/23/2006

## Section 1 - Chemical Product and Company Identification

Product Name: ET-050 Toner

Chemical Formula NA

CAS Number: NA (mixture)

General Use: Toner

Future Graphics LLC Part Numbers: HPU2MKI10KG

Company Name: Mitsubishi Kagaku Imaging Corporation Distributor: Future Graphics LLC.

Street Address: 401 Volvo Parkway

Street Address: 1175 Aviation Place

Town: Chesapeake

Town: San Fernando

State: Virginia

State: California

Zip Code: 23320

Zip Code: 91340

Emergency Contacts: Chemtrec 1-800-424-9300

Other Contacts: Future Graphics LLC. 800 / 394-9900

Health	1
Fire	1
Reactivity	0
PPE	(See Sec. 8)

## <<<>>> EMERGENCY OVERVIEW <<<>>>

This product may cause irritation of the respiratory system, eyes, and skin. This product is stable under normal conditions of use.

## Section 2 - Composition and Information on Ingredients

Ingredient	Iron Oxide - Black Pigment			CAS No.	Proprietary	% in Mixture	35-55
	OSHA	ACGIH	NIOSH	UNIT OF MEASURE			
TWA	10	5	5	mg/cu.meter			
STEL	NE	NE	NE	mg/cu.meter			
IDLH	NA	NA	2500	mg/cu.meter			

Ingredient	Styrene Acrylate Copolymer			CAS No.	Proprietary	% in Mixture	10-50
	OSHA	ACGIH	NIOSH	UNIT OF MEASURE			
TWA	NE	NE	NE	mg/cu.meter			
STEL	NE	NE	NE	mg/cu.meter			
IDLH	NA	NA	NE	mg/cu.meter			

Ingredient	Styrene Acrylate Copolymer			CAS No.	Proprietary	% in Mixture	10-50
	OSHA	ACGIH	NIOSH	UNIT OF MEASURE			
TWA	NE	NE	NE	mg/cu.meter			
STEL	NE	NE	NE	mg/cu.meter			
IDLH	NA	NA	NE	mg/cu.meter			

\* TOTAL DUST / INHALABLE DUST

\*\* RESPIRABLE DUST

\*\*\* Refer to Section 11 - Toxicological Information

### OVERALL MIXTURE:

This product is a mixture of dry chemical components. OSHA regulatory limits set for PARTICULATES NOT

OTHERWISE CLASSIFIED are: 15 mg/cu.meter for TOTAL DUST / INHALABLE DUST and 5 mg/cu.meter for RESPIRABLE DUST.

---

### Section 3 - Hazards Identification

**Primary Entry Routes:**

Absorption, Inhalation

**Target Organs:**

NA

**Inhalation Effects:**

Slight irritation of respiratory tract.

**Eye Effects:**

Dust may cause irritation by mechanical abrasion.

**Skin Effects:**

May cause skin irritation.

**Ingestion Effects:**

NA

**Carcinogenicity:**

NA

**Medical Conditions Aggravated by Long-term Exposure:**

Accumulation of dust in the respiratory system may cause moderate congestion.

**Chronic Effects and/or Recommendations:**

If use generates airborne particles, treat as a NUISANCE PARTICULATE (ACGIH TLV = 10 mg/cu. meter).

---

### Section 4 - First Aid Measures

**Inhalation:**

Protect yourself with appropriate PPE, remove the person to fresh air. Decontaminate and begin rescue breathing if breathing has stopped and CPR if heart action has stopped. Seek prompt medical attention.

**Eye:**

DO NOT allow victim to rub or keep eyes tightly shut. Gently lift eyelids and immediately flush eyes with large amounts of water. Remove any contact lenses. Continue to flush for at least 30 minutes, occasionally lifting the upper and lower lids. Seek prompt medical attention.

**Skin:**

Quickly remove contaminated clothing. Immediately wash area with large amounts of water. Seek prompt medical attention for any reddened skin other than from washing.

**Ingestion:**

Never give anything by mouth to an unconscious or convulsing person. Contact a Poison Control Center (PCC). Unless the PCC advises otherwise, have the conscious and alert person drink 1 to 2 glasses of water to dilute. Induce vomiting only after recent ingestions due to the possibility of seizures. Seek prompt medical attention.

**Additional First Aid Information:**

NA

---

### Section 5 - Fire Fighting Measures

<b>Flash Point:</b>		<b>Flash Point Method:</b>	
NA		NA	
<b>Flammability Classification:</b>		<b>Auto Ignition Temperature:</b>	
1 Slight (HMIS, NFPA)		ND	
<b>LEL:</b>	<b>UEL:</b>	<b>Burning Rate:</b>	
NA	NA	NA	

**Extinguishing Media:**

Water spray, dry chemical, foam, carbon dioxide, or halon-type extinguishers.

**Unusual Fire / Explosion Hazards:**

May form flammable dust-air mixture.

**Hazardous Combustion Products:**

Carbon monoxide, carbon dioxide, nitrogen oxide, and smoke. Under certain conditions some aliphatic aldehydes and carboxylic acids may form.

**Fire-Fighting Instructions:**

Do not release runoff from fire control methods to sewers or waterways.

**Fire-Fighting Equipment:**

Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

---

## Section 6 - Accidental Release Measures

**Containment Method:**

When cleaning up spilled material, keep unnecessary people away, isolate area, and deny entry until the spilled material has been removed. Scoop up material and place in a chemical waste container. Suction up remaining material using a high efficiency vacuum cleaner. Avoid suspending particles in the air. Extreme caution should be used as material presents a slip hazard.

**Reporting Requirements:**

Follow applicable OSHA regulations (29 CFR 1910.120).

---

## Section 7 - Handling and Storage

**Handling Precautions:**

Keep containers closed at all times. Avoid creating dust. Keep away from ignition sources.

**Storage Requirements:**

Product is prone to gradual oxidation which may reduce quality over time.

**Regulatory Requirements:**

Follow all applicable local, state, and Federal regulations.

---

## Section 8 - Exposure Controls and Personal Protection

**Ventilation**

The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release in order to maintain airborne concentrations of the product below OSHA PELs (See Section 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**Respiratory Protection**

IMPROPER USE OF RESPIRATORS IS DANGEROUS. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134 and 1910.137) and, if necessary, wear a NIOSH approved respirator. Select respirator based on its suitability to provide adequate worker protection for given work conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. WARNING! Air purifying respirators do not protect worker in oxygen-deficient atmospheres. If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit testing, periodic environmental monitoring, maintenance, inspection, cleaning and convenient, sanitary storage areas.

**Protective Clothing and Equipment**

Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear splash-proof chemical goggles and face shield when working with liquid, unless full facepiece respiratory protection is worn. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

**Safety Stations**

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

### Contaminated Equipment

Separate contaminated work clothes from street clothes. Launder before reuse. Remove material from your shoes and clean personal protective equipment. Never take home contaminated clothing.

### Comments

Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the restroom, or apply cosmetics.

### Additional Information

NA

---

## Section 9 - Physical and Chemical Properties

<b>Boiling Point:</b> NA	<b>Freezing or Melting Point:</b> NA	<b>Odor Threshold:</b> ND	<b>Physical State:</b> Solid
<b>Viscosity:</b> NA	<b>Refractive Index:</b> NA	<b>Vapor Density (Air = 1)</b> NA	<b>Appearance and Odor:</b> Black, free-flowing powder, odorless.
<b>% Volatiles:</b> NA	<b>Surface Tension:</b> NA	<b>Vapor Pressures:</b> NA	<b>Water Solubility:</b> Negligible
<b>Density:</b> 1.5-2.5	<b>Evaporation Rate:</b> NA	<b>Formula Weight:</b> NA	<b>Other Solubilities:</b> NA
<b>pH:</b> NA	<b>Specific Gravity where Water = 1 at 4 deg C</b> NA		<b>Additional Comments:</b> NA

---

## Section 10 - Stability and Reactivity

<b>Stability:</b> Stable under conditions of normal use.	<b>Polymerization:</b> Hazardous polymerization cannot occur.	<b>Hazardous Decomposition Products:</b> NA
---	--	--

**Chemical Incompatibilities:**  
NA

**Conditions to Avoid:**  
NA

**Other Comments:**  
NA

---

## Section 11 - Toxicological Information

Checked box indicates that related health effects criteria applies to the overall mixture.

Eye Effects       Acute Oral Effects       Acute Inhalation Effects       Mutagenicity   
Skin Effects       Chronic Effects       Carcinogenicity       Teratogenicity

**EXPLANATION of HEALTH EFFECTS:**

NA

**EXPLANATION of TOXICOLOGICAL CRITERIA:**

**Chemical Component:** Iron Oxide - Black Pigment

MAGNETITE: Toxicity Data: 400 mg/kg intrapleural-mouse TDLO

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: respiratory disorders

HEALTH EFFECTS:

INHALATION: MAGNETITE: See information on metal fume fever. Repeated or prolonged exposure, greater than 10 years, may cause siderosis, a benign pneumoconiosis. Chronic bronchitis has been associated with siderosis. Dyspnea may be pronounced and increases on exposure to irritants.

ACUTE EXPOSURE:

METAL FUME FEVER: Metal fume fever, an influenza-like illness, may occur due to the inhalation of freshly formed metal oxide particles sized below 1.5 microns and usually between 0.02-0.05 microns. Symptoms may be delayed 4-12 hours and begin with a sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms may include upper respiratory tract irritation accompanied by coughing and dryness of the mucous membranes, lassitude and a generalized feeling of malaise. Fever, chills, muscular pain, mild to severe headache, nausea, occasional vomiting, exaggerated mental activity, profuse sweating, excessive urination, diarrhea and prostration may also occur. Tolerance to fumes develops rapidly, but is quickly lost. All symptoms usually subside within 24-36 hours.

CHRONIC EXPOSURE:

METAL FUME FEVER: There is no form of chronic metal fume fever; however, repeated bouts with symptoms as described above are quite common. Resistance to the condition develops after a few days of exposure, but is quickly lost in 1 or 2 days.

SKIN CONTACT:

ACUTE EXPOSURE: MAGNETITE: May cause irritation.

CHRONIC EXPOSURE: MAGNETITE: No data available.

EYE CONTACT:

ACUTE EXPOSURE: MAGNETITE: May cause conjunctivitis, choroiditis, and retinitis. Iron particles embedded in eye tissue may cause ocular siderosis. Discoloration of the iris is one of the earliest symptoms. Siderosis may spread depending on the location of the particle. Rarely, ocular siderosis may cause glaucoma.

CHRONIC EXPOSURE: MAGNETITE: No data available.

INGESTION:

ACUTE EXPOSURE: MAGNETITE: No data available.

CHRONIC EXPOSURE: MAGNETITE: No data available.

---

**Chemical Component:** Styrene Acrylate Copolymer

Data Not Available

---

**Chemical Component:** Styrene Acrylate Copolymer

No data available.

---

---

## Section 12 - Ecological Information

Checked box indicates that information regarding the criteria applies to the overall mixture.

Ecotoxicity  Environmental Fate  Environmental Degradation  Soil Absorption and Mobility

**EXPLANATION of APPLICABLE ECOLOGICAL CRITERIA:**

NA

---

## Section 13 - Disposal Considerations

**Disposal:**

Waste material may be disposed of, incinerated, or recycled for its iron oxide under conditions that meet all Federal, State and Local regulations. Contact your supplier or a licensed contractor for detailed recommendations.

**Disposal Regulatory Requirements:**

NA

**Container Cleaning and Disposal:**

NA

### Section 14 - Transport Information

DOT Transportation Data (49CFR 172.101)		
<b>Shipping Name:</b> NA	<b>Label:</b> NA	<b>Passenger Air and Railcar:</b> NA
<b>Shipping Symbols:</b> NA	<b>Special Provisions:</b> NA	<b>Cargo Aircraft:</b> NA
<b>Hazard Class:</b> NA	<b>Exceptions:</b> NA	<b>Oceangoing Vessel Stowage:</b> NA
<b>ID Number:</b> NA	<b>Non-bulk Packaging:</b> NA	<b>Other:</b> NA
<b>Packing Group:</b> NA	<b>Bulk Packaging:</b> NA	

<b>EXPLANATION of APPLICATION TRANSPORTATION CRITERIA:</b>
--

NA

### Section 15 - Regulatory Information

Checked box(es) indicate that the chemical is subject to the associated regulatory requirements and/or appears on the associated chemical inventory list

<b>Chemical Component:</b> Iron Oxide - Black Pigment		<b>CAS #</b> Proprietary
40 CFR 261.33	<input type="checkbox"/> CAA 40 CFR 112	<input type="checkbox"/> TSCA inventory (US) <input checked="" type="checkbox"/>
40 CFR 261 classified	<input type="checkbox"/> SARA 40 CFR 311 and 312	<input type="checkbox"/> AICS inventory (Australia) <input checked="" type="checkbox"/>
RCRA Section 3001	<input type="checkbox"/> SARA 40 CFR 372.65	<input type="checkbox"/> EINECS inventory (Europe) <input checked="" type="checkbox"/>
CERCLA RQ established	<input type="checkbox"/> SARA 40 CFR 355	<input type="checkbox"/> DSL inventory (Canada) <input checked="" type="checkbox"/>
40 CFR 302.4	<input type="checkbox"/> OSHA 1910 1000 Z-1 tables	<input type="checkbox"/> ECL inventory (Korea) <input checked="" type="checkbox"/>
CWA 40 CFR 311( b)(4)	<input type="checkbox"/> OSHA 1910 subpart Z	<input type="checkbox"/> ENCS inventory (Japan) <input checked="" type="checkbox"/>
CWA 40 CFR 307(a)	<input type="checkbox"/>	<input type="checkbox"/> PICCS inventory (Phillipines) <input checked="" type="checkbox"/>
		<input type="checkbox"/> CHINA inventory
<b>Chemical Component:</b> Styrene Acrylate Copolymer		<b>CAS #</b> Proprietary
40 CFR 261.33	<input type="checkbox"/> CAA 40 CFR 112	<input type="checkbox"/> TSCA inventory (US) <input checked="" type="checkbox"/>
40 CFR 261 classified	<input type="checkbox"/> SARA 40 CFR 311 and 312	<input type="checkbox"/> AICS inventory (Australia) <input checked="" type="checkbox"/>
RCRA Section 3001	<input type="checkbox"/> SARA 40 CFR 372.65	<input type="checkbox"/> EINECS inventory (Europe) <input checked="" type="checkbox"/>
CERCLA RQ established	<input type="checkbox"/> SARA 40 CFR 355	<input type="checkbox"/> DSL inventory (Canada) <input checked="" type="checkbox"/>
40 CFR 302.4	<input type="checkbox"/> OSHA 1910 1000 Z-1 tables	<input type="checkbox"/> ECL inventory (Korea) <input checked="" type="checkbox"/>
CWA 40 CFR 311( b)(4)	<input type="checkbox"/> OSHA 1910 subpart Z	<input type="checkbox"/> ENCS inventory (Japan) <input checked="" type="checkbox"/>
CWA 40 CFR 307(a)	<input type="checkbox"/>	<input type="checkbox"/> PICCS inventory (Phillipines) <input checked="" type="checkbox"/>
		<input type="checkbox"/> CHINA inventory
<b>Chemical Component:</b> Styrene Acrylate Copolymer		<b>CAS #</b> Proprietary
40 CFR 261.33	<input type="checkbox"/> CAA 40 CFR 112	<input type="checkbox"/> TSCA inventory (US) <input checked="" type="checkbox"/>
40 CFR 261 classified	<input type="checkbox"/> SARA 40 CFR 311 and 312	<input type="checkbox"/> AICS inventory (Australia) <input checked="" type="checkbox"/>
RCRA Section 3001	<input type="checkbox"/> SARA 40 CFR 372.65	<input type="checkbox"/> EINECS inventory (Europe) <input checked="" type="checkbox"/>
CERCLA RQ established	<input type="checkbox"/> SARA 40 CFR 355	<input type="checkbox"/> DSL inventory (Canada) <input checked="" type="checkbox"/>
40 CFR 302.4	<input type="checkbox"/> OSHA 1910 1000 Z-1 tables	<input type="checkbox"/> ECL inventory (Korea) <input checked="" type="checkbox"/>
CWA 40 CFR 311( b)(4)	<input type="checkbox"/> OSHA 1910 subpart Z	<input type="checkbox"/> ENCS inventory (Japan) <input checked="" type="checkbox"/>
CWA 40 CFR 307(a)	<input type="checkbox"/>	<input type="checkbox"/> PICCS inventory (Phillipines) <input checked="" type="checkbox"/>
		<input type="checkbox"/> CHINA inventory

## Section 16 - Other Information

**Abbreviations:** ACGIH - American Conference of Governmental Industrial Hygienists  
IDLH - Immediately Dangerous to Life and Health  
NA - Not Applicable to the criteria OR Not Available  
ND- Not Determined OR Not Known  
NE - None established  
OSHA - Occupational Safety and Health Administration  
PEL - Permissible Exposure Limit  
RCRA - Resource Conservation Recovery Act  
STEL - Short Term Exposure Limit  
TLV - Threshold Limit Value  
TSCA - Toxic Substances Control Act  
TWA - Time Weighted Average

**Disclaimer:** Judgements as to the suitability of information herein are the purchaser's responsibility. Although reasonable care has been taken in the preparation of such information, Mitsubishi Chemical America, Inc. extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to the purchaser's intended purpose or for the consequences of its use.

**Additional Comments:** NA

**Revision Notes:** SK

<<<<< **END OF MSDS**>>>>>